



# ZTEC™ G Series Filter Cartridges

## *Absolute Rated Polyethersulfone Membrane Pleated Filter Cartridges*

### Product Specifications

**Media:** Asymmetric Polyethersulfone Membrane

**Inner core, end caps, cage:** Polypropylene

**Support layers:** Spunbonded Polypropylene

**Gaskets/O-Rings:**

Buna-N, EPDM, Silicone, Teflon Encapsulated  
Viton (O-Rings only), Viton

**Micron ratings:** 0.1, 0.2, 0.45, 0.65  $\mu\text{m}$

### Dimensions

**Nominal lengths:**

9.75" 10" 20" 30" 40"  
24.8 25.4 50.8 76.2 101.6 cm

**Outside diameter:** 2.7" (6.9 cm)

**Inside diameter:** 1.0" (2.54 cm)

**Surface area:** 7.0 ft<sup>2</sup> (0.65 m<sup>2</sup>) per 10" element


### Operating Parameters

**Maximum sustained operating temperature:**  
176°F (80°C) at 20 psid (1.38 bar)

**Maximum differential pressure:**  
80 psid @ 70°F (4.14 bar @ 21°C)  
40 psid @ 160°F (2.8 bar @ 71°C)

**Maximum reverse differential pressure:**  
40 psid @ 70°F (2.8 bar @ 21°C)

**Recommended change-out pressure:**  
35 psid (2.4 bar)



This pleated, disposable filter element is constructed of absolute rated, hydrophilic, asymmetric polyethersulfone membrane with extended filter area to allow for a high system flow rate.

### FEATURES & BENEFITS

- 7.0 ft<sup>2</sup> (0.65 m<sup>2</sup>) of membrane surface area per 10" element — High throughput, longer on-line service reduces costly maintenance time
- Absolute rated membrane from 0.1 to 0.65  $\mu\text{m}$
- Manufactured in an ISO Class 7 cleanroom environment
- 100% flushed with 18 M $\Omega$  -cm DI water and gross integrity tested
- Fixed pore construction eliminates dirt unloading as differential pressure increases
- Low extractables

### CERTIFICATIONS

- USP Class VI: Meets USP Class VI Biological Test for Plastics
- FDA Listed Materials: All materials comply with FDA Title 21 of the Code of Federal Regulations Sections 174.5, 177.1520, and 177.2440 as applicable for food and beverage contact.
- European Directive for Food Contact: European Regulation No. 1935/2004 and European Regulation 10/2011: Tested for migration behavior and is suitable for contact with all kinds of foodstuffs with minimal rinse-up. Data available upon request.

### TYPICAL APPLICATIONS


- Food and Beverage
- Filtration of acids and bases
- Cosmetics
- Inks
- Chemicals
- Ultra pure water
- Aqueous solutions

# PERFORMANCE SPECIFICATIONS

- Hot DI Water: Filter cartridge will withstand temperatures of 185°F (85°C) for up to 30 consecutive minutes.
- Cleaning/Sanitization: Compatible with most common chemical cleaning, sanitizing and sterilizing agents and with pH range from 1–14. Consult factory for specific compatibility information.
- Steam/Autoclave: Cartridges may be steamed or autoclaved for at least 50 thirty-minute cycles @ 275°F (135°C).

ZTEC G NOMENCLATURE INFORMATION								
Filter Type	Retention Rating (microns)		Nominal Length (inches)		End Configuration		Gasket or O-Ring	
ZTEC G Series	0.1	0.45	-5	-20	P	Double Open End	B Buna-N	
		0.2	0.65	-9.75*	-30	P2	226/Flat Single Open End	E EPDM
				-10	-40	P3	222/Flat Single Open End	S Silicone
						P7	226/Fin Single Open End	T Teflon encap. Viton (O-Rings only)
						P8	222/Fin Single Open End	V Viton
					AM	Single Open End, Internal O-Ring		
					NPC	Double Open End, Internal O-Ring		
Example: ZTEC G 0.1-10P7S								
ZTEC G	0.1		-10		P7		S	

\*Available only for DOE (P) configuration



## FOR MORE INFORMATION

Customer Service/Technical Support: 1-888-353-0303  
 Europe (UK): +44-1424-777791 | China: +86-21-5238-6576  
 Asia: +65-9635-7690

## GTX-258 10-16



## DISTRIBUTED BY

All information and recommendations appearing in this bulletin concerning the use of products described herein are based on tests believe to be reliable. However, It is the user's responsibility to determine the suitability for his own use of such products. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Graver Technologies as to the effects of such use or the results to be obtained. Graver Technologies assumes no liability arising out of the use by others of such products. Nor is the information herein to be construed as absolutely complete, since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or government regulations. ZTEC is a trademark of Graver Technologies, LLC.



Graver Technologies | 200 Lake Drive, Glasgow, DE 19702 | 302-731-1700 | 800-249-1990  
 Fax: 1-302-369-0938 | info@gravertech.com | www.gravertech.com

A member of The Marmon Group—A Berkshire Hathaway Company